

10 HP Open Rotary Screw

Basic Compressor Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME Powder coated air receiver
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin-on oil filter
- Spin-on separator
- TEFC drive motor (3 phase only)
- UL control components
- 220 PSI maximum working pressure

Platinum Compressor Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Tank discharge ball valve
- Freight pre-paid in the 48 states & southern Canada

78 dba

37 cfm @ 125 psi

35 cfm @ 150 psi

75 dba

40 cfm @ 125 psi

38 cfm @ 150 psi



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R101V80	1	208-230	80 Gallon Vertical	32	24	76	44	N/A
R103V80	3	208-230-460	80 Gallon Vertical	32	24	76	28	14
R101H80	1	208-230	80 Gallon Horizontal	60	24	45	44	N/A
R103H80	3	208-230-460	80 Gallon Horizontal	60	24	45	28	14

Add -P to model number to make Platinum model

No Start Up Kit Required ■ Optional Lifetime Parts Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 7-2024

